



**◆标准品一览表 / STANDARD SIZE**

额定电压 Rated Voltage (Vdc)	静电容量 Capacitance (uF)	外形尺寸 Size φDXL (mm)	额定纹波电流 Ripple Current (A.r.m.s 85°C, 120Hz)	额定电压 Rated Voltage (Vdc)	静电容量 Capacitance (uF)	外形尺寸 Size φDXL (mm)	额定纹波电流 Ripple Current (A.r.m.s 85°C, 120Hz)	
350	1800	51×98	7.8	500	1200	51×98	5.6	
	2200	51×118	8.7		1500	51×118	6.3	
	2700	51×138	9.8		1800	51×148	7.1	
	3300	51×148	10.8		2200	64×119	8.5	
	3900	64×119	12.9		2700	64×139	9.6	
	4700	64×139	14.3		3300	64×149	10.5	
	5600	77×121	17.8		3900	77×131	13.3	
	6800	64×189	17.7		4700	77×151	14.8	
	6800	77×141	19.8		4700	90×121	17.8	
	8200	77×151	21.8		5600	90×131	19.5	
	8200	90×121	25.8		6800	77×191	18.1	
	10000	77×191	24.6		6800	90×151	21.7	
	10000	90×141	28.8		8200	90×191	24.5	
	12000	90×191	30.6		10000	90×221	27.4	
	15000	90×191	36.2		12000	90×241	30.1	
18000	90×221	40.1	550	1800	64×119	6.0		
400	1500	51×98		6.9	2200	64×139	6.8	
	1800	51×118		7.7	2700	64×149	7.5	
	2200	51×138		8.6	3300	77×131	9.4	
	2700	51×148		9.5	3900	77×151	10.4	
	3300	64×119		11.5	4700	77×171	11.5	
	3900	64×139		12.7	4700	90×131	13.6	
	4700	64×149		13.8	5600	77×191	12.7	
	4700	77×121		15.8	5600	90×151	15.2	
	5600	64×189		15.4	6800	90×191	17.3	
	5600	77×141		17.5	8200	90×221	19.4	
	6800	77×151		19.2	10000	90×241	21.6	
	6800	90×121		22.9	580	1500	64×119	5.6
	8200	77×191		21.4		1800	64×139	6.3
	8200	90×141		25.4		2200	64×149	7.1
	10000	90×151	27.9	2700		77×131	8.8	
12000	90×191	31.5	3300	77×151		9.9		
15000	90×221	35.8	3900	77×171		11.0		
18000	90×241	38.9	3900	90×131		12.9		
450	1200	51×98	6.5	4700		77×191	12.2	
	1500	51×118	7.4	4700		90×151	14.5	
	1800	51×138	8.3	5600		90×191	16.3	
	2200	64×119	10.1	6800		90×221	18.4	
	2700	64×139	11.3	8200		90×241	20.4	
	3300	64×149	12.5					
	3900	77×121	15.3					
	4700	77×141	17.0					
	4700	90×121	18.1					
	5600	77×151	17.4					
	6800	77×191	19.2					
	6800	90×141	21.0					
	8200	90×191	25.1					
	10000	90×221	27.9					
	12000	90×241	30.0					

**◆螺栓紧固扭矩和允许电流值 / Tightening torque of bolt and Permissible current of terminal**

固定带用螺栓 Clamp Bolt	推荐紧固扭矩 Recommended Tightening torque
M3	0.6 [N·m]
M4	1.3 [N·m]

端子用 Terminal	推荐紧固扭矩 (允许值) Recommended Tightening torque (Permissible Range)	端子允许电流 Permissible Current of Terminal
M5	2.2(1.5~3.2) [N·m]	60 [A r.m.s.]